


## LIMEA MINI 45W hermetic lamp




CE

Power	<b>45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5400 lm (120°)</b>	Colour of light	<b>NW</b>
Beam angle	<b>120 °</b>	Degree of protection (IP)	<b>IP65</b>




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI028031NW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.98
Useful luminous flux*	5400 lm (120°)
Luminous flux**	5150 lm (360°)
Lamp efficacy	120 lm/W
Luminous intensity	1550 cd
Colour of light	NW
Beam angle	120 °
RA	>80
Light source included	Yes
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	1680 x 52 x 27 mm
Weight	0.5 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	Inside/Outside
Number of pieces on the packaging	30 pcs.
Made in	PRC
Other	dane na moduł Fi use=5400 P=45W



\*applies to the LED source used. \*\*Luminaire luminous flux