


LIMEA MINI 36W hermetic lamp




CE

Power	36 W	Voltage	230 V
Luminous flux*	4000 lm (360°)	Colour of light	NW
Beam angle	120 °	IK	07
Degree of protection (IP)	IP65		



See more on dedicated page 




 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI028030NW
Power	36 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	4000 lm (360°)
Luminous flux**	4000 lm (360°)
Lamp efficacy	111 lm/W
Colour of light	NW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	1223x53x28 mm
Weight	0.45 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Number of pieces on the packaging	30 pcs.
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux